



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

|   |           |   |
|---|-----------|---|
| <b>(51) International Patent Classification <sup>6</sup> :</b><br><b>A61F 2/06</b>  | <b>A1</b> | <b>(11) International Publication Number:</b> <b>WO 97/26840</b><br><b>(43) International Publication Date:</b> 31 July 1997 (31.07.97)   |
| <b>(21) International Application Number:</b> PCT/US97/00672<br><b>(22) International Filing Date:</b> 23 January 1997 (23.01.97)<br><br><b>(30) Priority Data:</b><br>60/010,686 26 January 1996 (26.01.96) US<br>60/017,479 26 April 1996 (26.04.96) US<br>60/017,415 8 May 1996 (08.05.96) US<br>60/024,110 16 August 1996 (16.08.96) US<br><br><b>(71) Applicant:</b> DEKA PRODUCTS LIMITED PARTNERSHIP<br>[US/US]; 340 Commercial Street, Manchester, NH 03101 (US).<br><br><b>(72) Inventors:</b> GRAY, Larry, B.; 15 Iris Drive, Merrimack, NH 03054 (US). ECKERT, Ann; 2902 Hermitage Avenue, Easton, PA 18045 (US). CHELAK, Todd; 199 C4 N. Beverwyck Road, Lake Hiawatha, NJ 07034 (US). TUMARKIN, Robert; 17 Augusta Avenue, Edison, NJ 08820 (US).<br><br><b>(74) Agents:</b> SUNSTEIN, Bruce, D. et al.; Bromberg & Sunstein, 125 Summer Street, Boston, MA 02110-1618 (US). |           | <b>(81) Designated States:</b> AU, CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).<br><br><b>Published</b><br><i>With international search report.</i><br><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> |
| <b>(54) Title:</b> AXIALLY FLEXIBLE STENT<br><br><b>(57) Abstract</b><br><p>A stent with axial flexibility, in a preferred embodiment, has a longitudinal axis and comprises a plurality of longitudinally disposed bands, wherein each band defines a generally continuous wave along a line segment parallel to the longitudinal axis. A plurality of links maintains the bands in a tubular structure. In a further embodiment of the invention, each longitudinally disposed band of the stent is connected, at a plurality of periodic locations, by a short circumferential link to an adjacent band.</p> <div data-bbox="743 1136 1437 1661" data-label="Image"> </div>  |           |   |

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

|    |                          |    |  |    |                          |
|----|--------------------------|----|--|----|--------------------------|
| AM | Armenia                  | GB | United Kingdom                           | MW | Malawi                   |
| AT | Austria                  | GE | Georgia                                  | MX | Mexico                   |
| AU | Australia                | GN | Guinea                                   | NE | Niger                    |
| BB | Barbados                 | GR | Greece                                   | NL | Netherlands              |
| BE | Belgium                  | HU | Hungary                                  | NO | Norway                   |
| BF | Burkina Faso             | IE | Ireland                                  | NZ | New Zealand              |
| BG | Bulgaria                 | IT | Italy                                    | PL | Poland                   |
| BJ | Benin                    | JP | Japan                                    | PT | Portugal                 |
| BR | Brazil                   | KE | Kenya                                    | RO | Romania                  |
| BY | Belarus                  | KG | Kyrgyzstan                               | RU | Russian Federation       |
| CA | Canada                   | KP | Democratic People's Republic<br>of Korea | SD | Sudan                    |
| CF | Central African Republic | KR | Republic of Korea                        | SE | Sweden                   |
| CG | Congo                    | KZ | Kazakhstan                               | SG | Singapore                |
| CH | Switzerland              | LI | Liechtenstein                            | SI | Slovenia                 |
| CI | Côte d'Ivoire            | LK | Sri Lanka                                | SK | Slovakia                 |
| CM | Cameroon                 | LR | Liberia                                  | SN | Senegal                  |
| CN | China                    | LT | Lithuania                                | SZ | Swaziland                |
| CS | Czechoslovakia           | LU | Luxembourg                               | TD | Chad                     |
| CZ | Czech Republic           | LV | Latvia                                   | TG | Togo                     |
| DE | Germany                  | MC | Monaco                                   | TJ | Tajikistan               |
| DK | Denmark                  | MD | Republic of Moldova                      | TT | Trinidad and Tobago      |
| EE | Estonia                  | MG | Madagascar                               | UA | Ukraine                  |
| ES | Spain                    | ML | Mali                                     | UG | Uganda                   |
| FI | Finland                  | MN | Mongolia                                 | US | United States of America |
| FR | France                   | MR | Mauritania                               | UZ | Uzbekistan               |
| GA | Gabon                    |    |  | VN | Viet Nam                 |

## AXIALLY FLEXIBLE STENT

5

### Technical Field

The present invention relates to a stent having axial flexibility and resilience in its expanded form.

### Background Art

10 A stent is commonly used as a tubular structure left inside the lumen of a duct to relieve an obstruction. Commonly, stents are inserted into the lumen in a non expanded form and are then expanded autonomously (Tihon et al. (1994) U.S. Patent No. 5,356,423) or with the aid of a second device *in situ*. A typical method of expansion occurs through the use of a catheter mounted angioplasty  
15 balloon which is inflated within the stenosed vessel or body passageway in order to shear and disrupt the obstructions associated with the wall components of the vessel and to obtain an enlarged lumen. In the absence of a stent, restenosis may occur as a result of elastic recoil of the stenotic lesion. Although a number of stent designs have been reported, these designs have suffered from a number of  
20 limitations. These include; restrictions on the dimension of the stent (Cardon et al. 1995 U.S. Patent No 5,383,892 ). Cardon et al. describes a stent that has rigid ends (8mm) and a flexible median part of 7-21mm. This device is formed of multiple parts and is not continuously flexible along the longitudinal axis. Another stent design that has rigid segments and flexible segments has been  
25 described by Pinchasik et al. US Patent 5,449,373 (1995).

Other stents are described as longitudinally flexible (Lau et al.(1995) U.S. Patent No. 5,421,955 also EP application 540290 A2, A3) but consist of a plurality of cylindrical elements connected by flexible members. This design has at least one important disadvantage, for example, according to this design, protruding  
30 edges occur when the stent is flexed around a curve raising the possibility of

inadvertent retention of the stent on plaque deposited on arterial walls. This may cause the stent to embolize or move out of position and further cause damage to the interior lining of healthy vessels. (see Figure 1(a) below).

Thus, stents known in the art, which may be expanded by balloon  
5 angioplasty, generally compromise axial flexibility to permit expansion and provide overall structural integrity.

### Summary of The Invention

The present invention overcomes some perceived shortcomings of prior  
10 art stents by providing a stent with axial flexibility. In a preferred embodiment, the stent has a first end and a second end with an intermediate section between the two ends. The stent further has a longitudinal axis and comprises a plurality of longitudinally disposed bands, wherein each band defines a generally continuous wave along a line segment parallel to the longitudinal axis. A  
15 plurality of links maintains the bands in a tubular structure. In a further embodiment of the invention, each longitudinally disposed band of the stent is connected, at a plurality of periodic locations, by a short circumferential link to an adjacent band. The wave associated with each of the bands has approximately the same fundamental spatial frequency in the intermediate section, and the  
20 bands are so disposed that the waves associated with them are spatially aligned so as to be generally in phase with one another. The spatially aligned bands are connected, at a plurality of periodic locations, by a short circumferential link to an adjacent band.

In particular, at each one of a first group of common axial positions, there  
25 is a circumferential link between each of a first set of adjacent pairs of bands.

At each one of a second group of common axial positions, there is a circumferential link between each of a second set of adjacent rows of bands, wherein, along the longitudinal axis, a common axial position occurs alternately in the first group and in the second group, and the first and second sets are  
30 selected so that a given band is linked to a neighboring band at only one of the

first and second groups of common axial positions.

In a preferred embodiment of the invention, the spatial frequency of the wave associated with each of the bands is decreased in a first end region lying proximate to the first end and in a second end region lying proximate to the second end, in comparison to the spatial frequency of the wave in the intermediate section. In a further embodiment of the invention, the spatial frequency of the bands in the first and second end regions is decreased by 20% compared with the spatial frequency of the bands in the intermediate section. The first end region may be located between the first end and a set of circumferential links lying closest to the first end and the second end region lies between the second end and a set of circumferential links lying closest to the second end. The widths of corresponding sections of the bands in these end regions, measured in a circumferential direction, are greater in the first and second end regions than in the intermediate section. Each band includes a terminus at each of the first and second ends and the adjacent pairs of bands are joined at their termini to form a closed loop.

In a further embodiment of the invention, a stent is provided that has first and second ends with an intermediate section therebetween, the stent further having a longitudinal axis and providing axial flexibility. This stent includes a plurality of longitudinally disposed bands, wherein each band defines a generally continuous wave having a spatial frequency along a line segment parallel to the longitudinal axis, the spatial frequency of the wave associated with each of the bands being decreased in a first end region lying proximate to the first end and in a second end region lying proximate to the second end, in comparison to the spatial frequency of the wave in the intermediate section; and a plurality of links for maintaining the bands in a tubular structure. The first and second regions have been further defined as the region that lies between the first and second ends and a set of circumferential links lying closest to the first end and second end.

In a further embodiment the widths of the sections of the bands, measured

in a circumferential direction, are greater in the first and second end regions than in the intermediate section.

### Brief Description of the Drawings

5       The foregoing aspects of the invention will be more readily understood by reference to the following detailed description, taken with the accompanying drawings, in which:

      Figs 1 (a) and 1 (b) are side views of a stent having circumferentially disposed bands wherein the stent is in axially unbent and bent positions  
10   respectively, the latter showing protruding edges.

      Figs 1 (c) and 1 (d) are side views of an axially flexible stent in accordance with the present invention wherein the stent is in unbent and bent positions respectively, the latter displaying an absence of protruding edges.

      Fig. 2 is a side view of a portion of the stent of Figs. 1(c) and 1(d) showing  
15   the longitudinal bands, spaces, and inner radial measurements of bends in the bands being measured in inches.

      Figs. 3 (a) and 3 (b) show a portion of the stent of Fig. 2 with two bands between two circumferential links (a) before expansion in the undeformed state; and (b) after expansion, in the deformed state.

20       Fig. 4 is a view along the length of a piece of cylindrical stent (ends not shown) prior to expansion showing the exterior surface of the cylinder of the stent and the characteristic banding pattern.

      Fig. 5 is an isometric view of a deflection plot where the stent of Fig. 2 is expanded to a larger diameter of 5mm.

25       Fig. 6 shows a two-dimensional layout of the stent of Fig. 4 to form a cylinder such that edge "A" meets edge "B", and illustrating the spring-like action provided in circumferential and longitudinal directions.

      Figure 7 shows a two dimensional layout of the stent. The ends are modified such that the length ( $L_A$ ) is about 20% shorter than length ( $L_B$ ) and the  
30   width of the band A is greater than the width of band B.

### Detailed Description of Specific Embodiments

Improvements afforded by embodiments of the present invention include (a) increased flexibility in two planes of the non-expanded stent while maintaining radial strength and a high percentage open area after expansion; (b) even pressure on the expanding stent that ensures the consistent and continuous contact of expanded stent against artery wall; (c) avoidance of protruding parts during bending; (d) removal of existing restrictions on maximum length of stent; and reduction of any shortening effect during expansion of the stent.

In a preferred embodiment of the invention, an expandable cylindrical stent is provided having a fenestrated structure for placement in a blood vessel, duct or lumen to hold the vessel, duct or lumen open, more particularly for protecting a segment of artery from restenosis after angioplasty. The stent may be expanded circumferentially and maintained in an expanded configuration, that is circumferentially rigid. The stent is axially flexible and when flexed at a band, the stent avoids any externally protruding component parts. Figure 1 shows what happens to a stent, of a similar design to a preferred embodiment herein but utilizing instead a series of circumferentially disposed bands, when caused to bend in a manner that is likely encountered within a lumen of the body. A stent with a circumferential arrangement of bands (1) experiences an effect analogous to a series of railroad cars on a track. As the row of railroad cars proceeds around the bend, the corner of each car proceeding around the bend after the coupling is caused to protrude from the contour of the track. Similarly, the serpentine circumferential bands have protrusions (2) above the surface of the stent as the stent bends. In contrast, the novel design of the embodiment shown in Figs. 1 (c) and 1 (d) and Figure 7 in which the bands (3) are axially flexible and are arranged along the longitudinal axis, avoids the box car effect when the stent is bent, so the bent bands (4) do not protrude from the profile of the curve of the stent. Furthermore, any flaring at the ends of the stent that might occur with a stent having a uniform structure is substantially eliminated by introducing a modification at the ends of the stent. This modification comprises decreasing the

spatial frequency and increasing the width of the corresponding bands in a circumferential direction ( $L_A$  and  $A$ ) compared to that of the intermediate section ( $L_B$  and  $B$ ). In an embodiment of the invention, the spatial frequency  $L_A$  may be decreased 0-50% with respect to  $L_B$ , and the width  $A$  may be increased in the  
5 range of 0-150% with respect to  $B$ . Other modifications at the ends of the stent may include increasing the thickness of the wall of the stent and selective electropolishing. These modifications protect the artery and any plaque from abrasion that may be caused by the stent ends during insertion of the stent. The modification also may provide increased radio-opacity at the ends of the stent.  
10 Hence it may be possible to more accurately locate the stent once it is in place in the body.

The embodiment as shown in Figs. 2 and 6 has the unique advantage of possessing effective "springs" in both circumferential and longitudinal directions shown as items (5) and (6) respectively. These springs provide the stent with the  
15 flexibility necessary both to navigate vessels in the body with reduced friction and to expand at the selected site in a manner that provides the final necessary expanded dimensions without undue force while retaining structural resilience of the expanded structure.

As shown in both Figs. 2, 4 and 6, each longitudinal band undulates  
20 through approximately two cycles before there is formed a circumferential link to an adjacent band. Prior to expansion, the wave associated with each of the bands may have approximately the same fundamental spatial frequency, and the bands are so disposed that the waves associated with them are spatially aligned, so as to be generally in phase with one another as shown in Fig. 6.

25 The aligned bands on the longitudinal axis are connected at a plurality of periodic locations, by a short circumferential link to an adjacent band. Consider a first common axial position such as shown by the line X-X in Fig. 4 and 6. Here an adjacent pair of bands is joined by circumferential link 7. Similarly other pairs of bands are also linked at this common axial position. At a second common axial  
30 position, shown in Fig. 6 by the line Y-Y, an adjacent pair of bands is joined by



circumferential link 8. However, any given pair of bands that is linked at X-X is not linked at Y-Y and vice-versa. The X-X pattern of linkages repeats at the common axial position Z-Z. In general, there are thus two groups of common axial positions. In each of the axial positions of any one group are links between  
5 the same pairs of adjacent bands, and the groups alternate along the longitudinal axis of the embodiment. In this way, circumferential spring 5 and the longitudinal spring 6 are provided.

A feature of the expansion event is that the pattern of open space in the stent of the embodiment of Fig. 2 before expansion is different from the pattern of  
10 the stent after expansion. In particular, in a preferred embodiment, the pattern of open space on the stent before expansion is serpentine, whereas after expansion, the pattern approaches a diamond shape (3a, 3b). In embodiments of the invention, expansion may be achieved using pressure from an expanding balloon or by other mechanical means.

15 In the course of expansion, as shown in Fig. 3, the wave shaped bands tend to become straighter. When the bands become straighter, they become stiffer and thereby withstand relatively high radial forces. Fig. 3 shows how radial expansion of the stent causes the fenestra to open up into a diamond shape with maximum stress being expended on the apices of the diamond along the  
20 longitudinal axis. When finite element analyses including strain studies were performed on the stent, it was found that maximum strain was experienced on the bands and links and was below the maximum identified as necessary to maintain structural integrity.

The optimization of strain of the stent is achieved by creating as large a  
25 turn radius as possible in the wave associated with each band in the non-expanded stent. This is accomplished while preserving a sufficient number of bands and links to preserve the structural integrity of the stent after expansion. In an embodiment of the invention, the strain may be less than 0.57 inches/inch for 316L stainless steel. The expansion pressure may be 1.0- 7.0 atmospheres. The  
30 number of bands and the spatial frequency of the wave on the longitudinal axis

also affects the number of circumferential links. The circumferential links contribute structural integrity during application of radial force used in expansion of the stent and in the maintenance of the expanded form. While not being limited to a single set of parameters, an example of a stent of the invention  
5 having a longitudinal axis and providing axial flexibility of the type shown in Figure 6, may include a stent having an expanded diameter of 4mm and a length of 30mm that for example may have about 8-12 rows, more particularly 10 rows and about 6-10 slots, more particularly 8 slots (a slot is shown in Figure 6 as extending between X and Z), with a wave amplitude of about  $1/4$ - $1/10$  of a slot  
10 length, more particularly  $1/8$  of a slot length.

The stent may be fabricated from many methods. For example, the stent may be fabricated from a hollow or formed stainless steel tube that may be cut out using lasers, electric discharge milling (EDM), chemical etching or other means. The stent is inserted into the body and placed at the desired site in an  
15 unexpanded form. In a preferred embodiment, expansion of the stent is effected in a blood vessel by means of a balloon catheter, where the final diameter of the stent is a function of the diameter of the balloon catheter used.

In contrast to stents of the prior art, the stent of the invention can be made at  
20 any desired length, most preferably at a nominal 30mm length that can be extended or diminished by increments, for example 1.9mm increments.

It will be appreciated that a stent in accordance with the present invention may be embodied in a shape memory material, including, for example, an appropriate alloy of nickel and titanium; or stainless steel. In this embodiment  
25 after the stent has been formed, it may be compressed so as to occupy a space sufficiently small as to permit its insertion in a blood vessel or other tissue by insertion means, wherein the insertion means include a suitable catheter, or flexible rod. On emerging from the catheter, the stent may be configured to expand into the desired configuration where the expansion is automatic or  
30 triggered by a change in pressure, temperature or electrical stimulation.

An embodiment of the improved stent has utility not only within blood vessels as described above but also in any tubular system of the body such as the bile ducts, the urinary system, the digestive tube, and the tubes of the reproductive system in both men and women.

What is claimed is:

1. A stent having first and second ends with an intermediate section therebetween, the stent further having a longitudinal axis and providing axial  
5 flexibility, comprising:  
a plurality of longitudinally disposed bands, wherein each band defines a generally continuous wave having a spatial frequency along a line segment parallel to the longitudinal axis; and  
a plurality of links for maintaining the bands in a tubular structure.  
10
2. A stent according to claim 1, wherein each band is connected, at a plurality of periodic locations, by a short circumferential link to an adjacent band.
3. A stent according to claim 1, wherein the wave associated with each of  
15 the bands has approximately the same fundamental spatial frequency for the intermediate section.
4. A stent according to claim 3, wherein the bands are so disposed that the waves associated with them are spatially aligned so as to be generally in phase  
20 with one another.
5. A stent according to claim 4, wherein the spatially aligned bands are connected, at a plurality of periodic locations, by a short circumferential link to an adjacent band.  
25
6. A stent according to claim 5, wherein, at each one of a first group of common axial positions, there is a circumferential link between each of a first set of adjacent pairs of bands.
- 30 7. A stent according to claim 5, wherein, at each one of a second group of

common axial positions, there is a circumferential link between each of a second set of adjacent rows of bands, wherein, along the longitudinal axis, a common axial position occurs alternately in the first group and in the second group, and the first and second sets are selected so that a given band is linked to a  
5 neighboring band at only one of the first and second groups of common axial positions.

8. A stent according to claim 2, wherein the spatial frequency of the wave associated with each of the bands, is decreased in a first end region lying  
10 proximate to the first end and in a second end region lying proximate to the second end, in comparison to the spatial frequency of the wave in the intermediate section.

9. A stent according to claim 8, wherein the spatial frequency is decreased  
15 by about 20 % compared with the spatial frequency of the wave in the intermediate section.

10. A stent according to claim 8, wherein the first end region lies between the first end and a set of circumferential links lying closest to the first end and the  
20 second end region lies between the second end and a set of circumferential links lying closest to the second end.


11. A stent according to claim 8, wherein widths of corresponding sections of the bands, measured in a circumferential direction, are greater in the first and  
25 second end regions than in the intermediate section.

12. A stent according to claim 10, wherein widths of corresponding sections of the bands, measured in a circumferential direction, are greater in the first and second end regions than in the intermediate section.


13. A stent according to claim 1, wherein each band includes a terminus at each of the first and second ends and the adjacent pairs of bands are joined at their termini to form a closed loop.
- 5        14. A stent according to claim 8, wherein each band includes a terminus at each of the first and second ends and the adjacent pairs of bands are joined at their termini to form a closed loop.
- 10       15. A stent according to claim 9, wherein the first end region lies between the first end and a set of circumferential links lying closest to the first end and the second end region lies between the second end and a set of circumferential links lying closest to the second end.
- 15       16. A stent according to claim 15, wherein widths of corresponding sections of the bands, measured in a circumferential direction, are greater in the first and second end
- 20       17. A stent according to claim 7, wherein the spatial frequency of the wave associated with each of the bands, is decreased in a first end region lying proximate to the first end and a second end region lying proximate to the second end, in comparison to the spatial frequency of the wave in the intermediate section.
- 25       18. A stent having first and second ends with an intermediate section therebetween, the stent further having a longitudinal axis and providing axial flexibility, comprising:  
a plurality of longitudinally disposed bands, wherein each band defines a generally continuous wave having a spatial frequency along a line segment parallel to the longitudinal axis; the spatial frequency of the wave associated with  
30 each of the bands being decreased in a first end region lying proximate to the first

end and in a second end region lying proximate to the second end, in comparison to the spatial frequency of the wave in the intermediate section; and  
a plurality of links for maintaining the bands in a tubular structure.

- 5        19. A stent according to claim 18, wherein widths of sections of the bands, measured in a circumferential direction, are greater in the first and second end regions than in the intermediate section.









⑦


a).


UNDEFORMED


(b)


DEFORMED

FINITE ELEMENT MODEL  
IS ONLY  $\frac{1}{2}$  OF THE PATTERN.









# INTERNATIONAL SEARCH REPORT

Int. Application No.  
PCT/US 97/00672

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages                          | Relevant to claim No. |
|------------|---|-----------------------|
| P,X        | EP 0 734 698 A (VARIMED) 2 October 1996<br>see column 8, line 21 - column 9, line 10;<br>figures 6-8        | 1-3,13                |
| A          | US 5 449 373 A (PINCHASIK ET AL.) 12<br>September 1995<br>cited in the application<br>see abstract; figures | 1                     |



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

28 May 1997

Date of mailing of the international search report

04.06.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+ 31-70) 340-3016

Authorized officer

Hagberg, A

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/00672

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|---|---------------------|----------------------------|---------------------|
| EP 734698 A                               | 02-10-96            | DE 19512066 A              | 28-11-96            |
|   |                     | DE 19540851 A              | 07-05-97            |
|   |                     | DE 19516191 A              | 06-02-97            |
|   |                     | JP 9010318 A               | 14-01-97            |
| -----                                     |                     |                            |                     |
| US 5449373 A                              | 12-09-95            | WO 9633671 A               | 31-10-96            |
|   |                     | AU 2427995 A               | 18-11-96            |
| -----                                     |                     |                            |                     |